

# Eaton SMS24RE3TR29

Catalog Number: SMS24RE3TR29

Straight boardmount with long PCB female contacts (Tin plating);  
SMS24RE3TR29

## General specifications

Product Name	Catalog Number
Eaton Souriau SMS series quick mating plastic rectangular connector	SMS24RE3TR29
	Product Length/Depth
	13.4 mm
Product Height	Product Width
21.2 mm	31.2 mm
Product Weight	
15.2 g	

## Product specifications

### Environmental conditions

REACH

Flammability rating UL94 V0

### Connector accessory option

No backshell possibility

### Connector type

Receptacle

### Contact delivery

Loaded

### Contact plating

Tin pre plated

### Contact type

PCB

### Coupling type

Push-Pull

### Degree of protection

IP30

### Layout

24

### Shell material

Plastic

### Operating temperature - max

125 °C

### Operating temperature - min

-55 °C

### Receptacle type

Front Mount Panel

### Number Of Contacts

24

### Number of cavity #16

24

## Resources

### Drawings

[BSA20192702400.pdf](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)