

Eaton SMS6RE3TR29

Catalog Number: SMS6RE3TR29

Straight boardmount with long PCB female contacts (Tin plating);
SMS6RE3TR29

General specifications



Product Name	Catalog Number
Eaton Souriau SMS series quick mating plastic rectangular connector	SMS6RE3TR29
Product Height	Product Length/Depth
16.2 mm	13.4 mm
Product Weight	Product Width
4.7 g	10.9 mm

Product specifications

Environmental conditions

Flammability rating UL94 V0

REACH

Connector accessory option

No backshell possibility

Connector type

Receptacle

Contact delivery

Loaded

Contact plating

Tin pre plated

Contact type

PCB

Coupling type

Push-Pull

Degree of protection

IP30

Layout

6

Shell material

Plastic

Operating temperature - max

125 °C

Operating temperature - min

-55 °C

Receptacle type

Front Mount Panel

Number Of Contacts

6

Number of cavity #16

6

Resources

Drawings

[BSA20192702400.pdf](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)